



SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label : Thurmalox 2600-00
Product Code(s) : 2600-00

Recommended use of the chemical and restrictions on use

: High Temperature Coating
Use pattern: Professional Use Only
Recommended restrictions: None Known.

Chemical family : Mixture.

Name, address, and telephone number of the manufacturer:

Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A. 02149

Email: sales@dampney.com
Supplier's Telephone #: (617) 389-2805
24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.)

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

White liquid - Solvent odor.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification:

Flammable Liquid - Category 3 Carcinogen - Category 2 Reproductive Toxicity - Category 1B

Label elements

Hazard pictogram(s)



Signal Word
DANGER!

Hazard statement(s)

Flammable liquid and vapor. Suspected of causing cancer.
May damage fertility or the unborn child.

Precautionary statement(s)

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/Bond container and receiving equipment.
Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools.
Take precautionary measures against static discharge. Wear protective gloves/clothing and eye/face protection.

If exposed or concerned: Get medical attention/advice.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. In case of fire: Use alcohol-resistant foam, carbon dioxide or dry chemical to extinguish.

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.



SAFETY DATA SHEET

Other hazards

No OSHA defined hazard classes.

Other hazards which do not result in classification: Burning produces obnoxious and toxic fumes. Direct eye contact may cause slight or mild, transient irritation. Ingestion can cause gastrointestinal irritation, nausea, and diarrhea. Direct skin contact may cause slight or mild, transient irritation. Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Environmental precautions: Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

| Chemical name | Common name and synonyms | CAS # | Concentration (% by weight) |
|--------------------------------|------------------------------|----------|-----------------------------|
| Glycol monoethyl ether acetate | 2-Ethoxyethyl acetate; EGEEA | 111-15-9 | 25.0 - 30.0 |
| Ethylbenzene | Ethylbenzol Phenylethane | 100-41-4 | 0.1 - 1.0 |

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion :

IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting. Material is an aspiration hazard. Guard against aspiration into lungs by having the individual turn on their left side. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

Inhalation:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact :

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Eye contact :

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation develops and persists.

Most important symptoms and effects, both acute and delayed

: May cause respiratory irritation. Symptoms may include upper respiratory irritation, coughing and breathing difficulties. May cause drowsiness and dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Causes skin irritation. Symptoms may include redness, itching and swelling. Direct eye contact may cause slight or mild, transient irritation. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Suspected of causing cancer. May damage fertility.

Indication of any immediate medical attention and special treatment needed

: Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media:

Do not use water jet, as this may spread burning material.

Special hazards arising from the substance or mixture / Conditions of flammability: Flammable liquid and vapor. Keep away from heat and flame. This product will accumulate static charge by flow, splashing or agitation. Vapors may travel considerable distance to a source of ignition and flash back. Vapours are heavier than air and collect in confined and low-lying areas. Product may float, and be re-ignited at the water's surface. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

: Flammable Liquids - Category 3

Hazardous combustion products:

Carbon oxides ; Other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters



SAFETY DATA SHEET

: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures:

Move containers from fire area if safe to do so. Use water spray to cool unopened containers. Avoid spreading burning liquid with water spray used for cooling purposes. Do not allow run-off from fire fighting to enter drains or water courses. Prevent fire extinguishing water from contaminating surface water or the ground water system.
 Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid breathing vapour or mist. Restrict access to area until completion of clean-up. Remove all sources of ignition. All persons dealing with the clean-up should wear the appropriate personal protective equipment. For personal protection see section 8.

Environmental precautions :

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up:

Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Bond and ground transfer containers and equipment to avoid static accumulation. Contaminated absorbent material may pose the same hazards as the spilled product. Pick up and transfer to properly labeled containers. Contact the proper local authorities.

Special spill response procedures

: In case of a transportation accident, in the United States contact CHEMTREC at 1-800-424-9300 or International at 1-703-527-3887.

EPA/CERCLA Reportable quantity (RQ): Ethylbenzene (1000 lbs / 454 kg)

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat and flame. Use in a well-ventilated area. Keep container tightly closed. Bond and ground transfer containers and equipment. Use explosion-proof electrical and ventilating equipment. Use non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/clothing and eye/face protection. Avoid breathing vapour or mist. Do not ingest. Avoid contact with skin, eyes and clothing. Avoid contact with incompatible materials. Encourage good housekeeping and personal hygiene.

Conditions for safe storage

: Store in well-ventilated place. Keep cool. Store locked up. Keep container tightly closed. Store away from incompatibles and out of direct sunlight. Take measures to prevent the build up of electrostatic charge. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

Incompatible materials

: Strong oxidizers, acids and bases.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

| Chemical Name | ACGIH TLV | | OSHA | |
|--------------------------------|--------------|------|--|------|
| | TWA | STEL | PEL | STEL |
| Glycol monoethyl ether acetate | 5 ppm (skin) | N/Av | 100 ppm ; 540 mg/m ³ (skin) | N/Av |
| Ethylbenzene | 20 ppm | N/Av | 100 ppm (435 mg/m ³) | N/Av |

Exposure controls

Ventilation and engineering measures

: Use only outdoors or in a well-ventilated area. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection: If engineering controls and work practices are not effective in controlling exposure to this material, then wear



SAFETY DATA SHEET

suitable approved respiratory protection. If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection

: Wear protective gloves. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye / face protection

: Chemical splash goggles are recommended.

Other protective equipment : Ensure that eyewash stations and safety showers are close to the workstation location.

Other equipment may be required depending on workplace standards.

General hygiene considerations

: Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--|
| Appearance | : White liquid. |
| Odour | : Solvent odor. |
| Odour threshold | : N/Av |
| Ph | : N/Av |
| Melting/Freezing point | : N/Av |
| Initial boiling point and boiling range | : 136.11- 156.11°C (277-313.3°F) |
| Flash point | : 52.2oC (126oF) |
| Flashpoint (Method) | : Closed cup |
| Evaporation rate (BuAe = 1) | : 0.58 times slower than n-Butyl acetate |
| Flammability (solid, gas) | : N/Av |
| Lower flammable limit (% by vol.) | : N/Av |
| Upper flammable limit (% by vol.) | : N/Av |
| Oxidizing properties | : None known |
| Explosive properties | : Not explosive |
| Vapour pressure | : N/Av |
| Vapour density | : >1 |
| Relative density / Specific gravity | : 1.437 |

| | |
|---|--------|
| Solubility in water | : N/Av |
| Other solubility(ies) | : N/Av |
| Partition coefficient: n-octanol/water or Coefficient of water/oil distribution | : N/Av |

| | |
|------------------------------------|-----------------------|
| Auto-ignition temperature | : N/Av |
| Decomposition temperature | : N/Av |
| Viscosity | : 300 cSt at 40°C 47% |
| Volatiles (% by weight) | : 47% |
| Volatile organic Compounds (VOC's) | : 3 lbs/gal |

Other physical/chemical comments : None reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

| | |
|--|--|
| Reactivity: | Not normally reactive. |
| Chemical stability: | Stable under normal conditions. |
| Possibility of hazardous reactions: | Hazardous polymerization does not occur. May be sensitive to static discharge. |
| Conditions to avoid: | Keep away from heat, sparks and flame. Take precautionary measures against static discharge. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas. Avoid contact with incompatible materials. |
| Incompatible materials: | Strong oxidizers, acids and bases. |
| Hazardous decomposition products: | See Section 5 (Fire Fighting Measures). |

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:



SAFETY DATA SHEET

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption
: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: May cause respiratory irritation. Symptoms may include sore throat, running nose and shortness of breath.

Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Causes symptoms similar to those listed for inhalation.

Sign and symptoms skin

: Direct skin contact may cause slight or mild, transient irritation.

Sign and symptoms eyes

: Direct eye contact may cause slight or mild, transient irritation.

Potential Chronic Health Effects

: Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Mutagenicity: Not expected to be mutagenic in humans.

Carcinogenicity: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Carcinogenicity - Category 2 Suspected of causing cancer. Contains Ethylbenzene. Ethylbenzene is classified as carcinogenic by IARC (Group 2B) and ACGIH (Category A3).

Reproductive effects & Teratogenicity

: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Reproductive Toxicity-Category 1 May damage fertility.

Sensitization to material: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects: This material is not classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials: None reported by the manufacturer.

Toxicological data: There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

ATE oral = 10691.52 mg/kg

ATE inhalation (vapours) = 42.80 mg/L

| Chemical name | LC50(4hr) inh, rat | LD50 | |
|--------------------------------|-------------------------------|-------------|------------------|
| | | (Oral, rat) | (Rabbit, dermal) |
| Glycol monoethyl ether acetate | 11.6 mg/L | 2900 mg/kg | 10000 mg/kg |
| Ethylbenzene | 4000 ppm (17.4 mg/L) (vapour) | 3500 mg/kg | 15 380 mg/kg |

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: Should not be released into the environment. See the following tables for the substance's ecotoxicity data.

Ecotoxicity data:

| Ingredients | CAS No | Toxicity to Fish | | |
|--------------------------------|----------|----------------------------|-------------------|----------|
| | | LC50 / 96h | NOEC / 21 day | M Factor |
| Glycol monoethyl ether acetate | 111-15-9 | 42.2 mg/L (Fathead minnow) | N/Av | None. |
| Ethylbenzene | 100-41-4 | 4.2 mg/L (Rainbow trout) | 1.13 mg/L/30 days | None. |

| Ingredients | CAS No | Toxicity to Daphnia | | |
|-------------|--------|---------------------|---------------|----------|
| | | EC50 / 48h | NOEC / 21 day | M Factor |



SAFETY DATA SHEET

| | | | | |
|--------------------------------|----------|---------------------------|------|-------|
| Glycol monoethyl ether acetate | 111-15-9 | N/Av | N/Av | None. |
| Ethylbenzene | 100-41-4 | 1.81 mg/L (Daphnia magna) | N/Av | None. |

| Ingredients | CAS No | Toxicity to Algae | | |
|--------------------------------|----------|-----------------------------|-------------------|----------|
| | | EC50 / 96h or 72h | NOEC / 96h or 72h | M Factor |
| Glycol monoethyl ether acetate | 111-15-9 | N/Av | N/Av | None. |
| Ethylbenzene | 100-41-4 | 3.6 mg/L/96hr (Green algae) | 3.4 mg/L/96hr | None. |

Persistence and degradability

: No data is available on the product itself.

Bioaccumulation potential

: No data is available on the product itself.

| Components | Partition coefficient n-octanol/water (log Kow) | Bioconcentration factor (BCF) |
|---|---|-------------------------------|
| Glycol monoethyl ether acetate CAS 111-15-9 | 0.24 | N/Av |
| Ethylbenzene CAS 100-41-4 | 3.15 | 15 species: fish |

Mobility in soil:

No data is available on the product itself.

Other Adverse Environmental effects:

None known or reported by the manufacturer.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal: Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8.

Methods of Disposal: Dispose in accordance with all applicable regulations.

RCRA: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORTATION INFORMATION

| Regulatory Information | UN Number | UN proper shipping name | Transport hazard class(es) | Packing Group | Label |
|-------------------------------|--|-------------------------|----------------------------|---------------|-------|
| 49CFR/DOT | UN1263 | Paint | 3 | III | |
| Additional information | When transported as a limited quantity the maximum net capacity specified in 173.150(b)(2) of the subchapter 49CFR for inner packagings may be increased to 5L (1.3 gallons) 172.102(C)(1)(149) special provision 149. | | | | |
| TDG | UN1263 | Paint | 3 | III | |
| Additional information | May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass. | | | | |
| IMDG | UN1263 | Paint | 3 | III | |
| Additional information | May be shipped as a Limited Quantity when transported in containers no larger than 5 L (1.3 gallons); in packages not exceeding 30 kg (66 pounds) gross mass. | | | | |
| ICAO/IATA | UN1263 | Paint | 3 | III | |
| Additional information | Refer to ICAO/IATA Packing Instruction. | | | | |

Special precautions for user

: Keep away from heat, sparks and open flame. - No smoking.



SAFETY DATA SHEET

Environmental hazards: See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
 : Not available.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

| Ingredients | CAS # | TSCA Inventory | CERCLA Reportable Quantity (RQ) (40CFR 117.302): | SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355: | SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical | |
|--------------------------------|----------|----------------|--|--|---|--------------------------|
| | | | | | Toxic Chemical | de minimus Concentration |
| Glycol monoethyl ether acetate | 111-15-9 | Yes | N/Ap | N/Av | No | N/Ap |
| Ethylbenzene | 100-41-4 | Yes | 1000 lb/ 454 kg | None. | Yes | 0.1% |

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

| Ingredients | CAS # | California Proposition 65 | | State "Right to Know" Lists | | | | | |
|--------------------------------|----------|---------------------------|--|-----------------------------|-----|-----|-----|-----|-----|
| | | Listed | Type of Toxicity | CA | MA | MN | NJ | PA | RI |
| Glycol monoethyl ether acetate | 111-15-9 | No | Developmental Toxicity; male reproductive toxicity | Yes | Yes | Yes | Yes | Yes | Yes |
| Ethylbenzene | 100-41-4 | Yes | Cancer | Yes | Yes | Yes | Yes | Yes | Yes |

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).
 WHMIS Classification: See Section 2.

International Information:

Components listed below are present on the following International Inventory list:

| Ingredients | CAS # | European EINECS | Australia AICS | Philippines PICCS | Japan ENCS | Korea KECI/KECL | China IECSC | New Zealand IOC |
|--------------------------------|----------|-----------------|----------------|-------------------|----------------|-----------------|-------------|-----------------|
| Glycol monoethyl ether acetate | 111-15-9 | 203-839-2 | Present | Present | (2)-740 | KE-13668 | Present | HSR001157 |
| Ethylbenzene | 100-41-4 | 202-849-4 | Present | Present | (3)-60; (3)-28 | KE-13532 | Present | HSR001151 |

SECTION 16. OTHER INFORMATION

Legend:

- ACGIH: American Conference of Governmental Industrial Hygienists
- AICS: Australian Inventory of Chemical Substances
- CA: California
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- CSA: Canadian Standards Association
- DOT: Department of Transportation
- EC50: Effective Concentration 50%.
- EINECS: European Inventory of Existing Commercial chemical Substances
- ENCS: Existing and New Chemical Substances
- EPA: Environmental Protection Agency



SAFETY DATA SHEET

HMIS: Hazardous Materials Identification System
HSDB: Hazardous Substances Data Bank
IARC: International Agency for Research on Cancer
IECSC: Inventory of Existing Chemical Substances
IMDG: International Maritime Dangerous Goods
Inh: Inhalation
KECI: Korean Existing Chemicals Inventory
KECL: Korean Existing Chemicals List
LC: Lethal Concentration
LD: Lethal Dose
N/Ap: Not Applicable
N/Av: Not Available
NFFPA: National Fire Protection Association
NJ: New Jersey
NIOSH: National Institute of Occupational Safety and Health
NOEC: No observable effect concentration
NTP: National Toxicology Program
OECD: Organisation for Economic Co-operation and Development
OSHA: Occupational Safety and Health Administration
PA: Pennsylvania
PEL: Permissible exposure limit
PICCS: Philippine Inventory of Chemicals and Chemical Substances
RCRA: Resource Conservation and Recovery Act
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TPQ: Threshold Planning Quantity
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

References:

Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2015 (Chempendium, RTECs, HSDB, INCHEM).
OECD- The Global Portal to Information on Chemical Substances - eChemPortal, 2015
European Chemicals Agency, Classification Legislation, 2015 Material Safety Data Sheet from manufacturer.

Preparation Date (mm/dd/yyyy): 09/14/2021

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

| | |
|---|--|
| <p>Dampney Company, Inc. 85 Paris Street Everett MA 02149 U.S.A Telephone: (617) 389-2805 www.dampney.com</p> |  |
|---|--|

DISCLAIMER

This Safety Data Sheet was prepared by Dampney Company, Inc. and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Dampney Company, Inc. expressly disclaims all expressed or implied warranties and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process. This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Dampney Company, Inc.

END OF DOCUMENT